

In the Claims:

Please amend Claims 1, 5, 13, 27-28 and 30-31; and add new Claim 43, all as shown below. Applicant respectfully reserves the right to prosecute any originally presented claims in a continuing or future application.

1. (Currently Amended): A system for providing a sequence of content in a modular presentation system, comprising:

a plurality of display devices, wherein each display device includes a corresponding plurality of a processor and memory system to control each corresponding display device, and wherein each display device neighbors at least one other display device and at least three of the plurality of display devices are in visual proximity to each other;

an input device that receives input of a gesture to move a first content from a first display device of the plurality of display devices to a second display device, wherein a second content of the second display device is moved from the second display device of the plurality of display devices to a third display device, wherein a propagation order of ~~[[the]]~~ a third content followed by the second content followed by the first content represents the sequence; and

~~[[a]] wherein the processor corresponding to the first display device, that~~

interprets a direction to move the first content from the first display device based on the gesture, wherein the gesture is made with a flick which indicates content to be moved and a direction without designating ~~[[the]]~~ a destination display device,

determines the destination display device wherein the gesture specifies the second display device to which the first content is to be moved, based on the direction indicated by the gesture and the position of the plurality of display devices, wherein the destination display device is the second display device, that

establishes a peer-to-peer connection between the first display device and the second display device,

propagates the first content of the first display device to the second display device using the peer-to-peer connection, ~~and that~~

propagates the second content of the second display device to the third display device, wherein the third display device is determined based on the direction indicated by the gesture, and

wherein initiating the gesture changes the content displayed on all of the first display device, the second display device and the third display device.

2. (Previously Presented): The system of claim 1 wherein each of the plurality of display devices is configured to:

receive new content identification information;
transmit old content identification information; and
present content associated with the new content identification information.

3. (Previously Presented): The system of claim 2 wherein new content identification information is received from a processor associated with a neighboring display device in the reverse propagation direction, the old content identification information is transmitted to a processor associated with a neighboring display device in the forward propagation direction, the forward propagation direction derived from the gesture input.

4. (Previously Presented): The system of claim 2 wherein receiving new content identification information includes:

retrieving new content identification information from a memory stack.

5. (Currently Amended): A method of providing content in a modular presentation system having a plurality of display devices, wherein each display device includes a corresponding plurality of a processor and memory system to control each corresponding display device, and wherein at least three of the plurality of display devices are in visual proximity to each other, the method comprising:

receiving input of a gesture to move a sequence of content including a first content and a second content, wherein the first content is presented on a first display device of the plurality of display devices, wherein the gesture initiates propagation of content from right to left which indicates content to be moved and a direction without designating [[the]] a destination display device;

interpreting a direction to move the first content from the first display device based on the gesture;

~~specifying a second~~ determining the destination display device to which the first content is to be moved based on the direction indicated by the gesture and the relative position of the plurality of display devices, wherein the destination display device is a second display device, and determining a third display device to which the second content is to be moved based on the

direction indicated by the gesture and the relative position of the plurality of display devices,
wherein the first display device is on the right of the second display device and the second
display device is on the right of the third display device;~~and~~

establishing a peer-to-peer connection between the first display device and the second
display device;

propagating the first content of the first display device to the second display device using
the peer-to-peer connection,

propagating the second content of the second display device to the third display device,
and

presenting the first content at the second display device and the second content at the
third display device, wherein initiating the gesture simultaneously changes the content displayed
at both the first display device, and the second display device and the third display device.

6. (Original): The method of claim 5 wherein receiving gesture input includes:
receiving input on a touch screen display.

7-8. (Canceled)

9. (Previously Presented): The method of claim 5 wherein presenting the second content
at the third display device includes retrieving a second URL and sending the second URL to the
third display device.

10. (Previously Presented): The method of claim 5 wherein presenting the first content at the
second display device includes sending a first URL to the second display device.

11-12. (Canceled)

13. (Currently Amended): A computer readable medium with instructions for execution by a
computer for providing a sequence of content in a modular presentation system having a
plurality of display devices, wherein each display device includes a corresponding plurality of a
processor and memory system to control each corresponding display device, and wherein at
least two of the plurality of display devices are in physical and visual proximity to each other, the
instructions comprising:

receiving input of a gesture to move a first content presented on a first display device, wherein the gesture indicates content to be moved and a direction without designating a destination display device, and wherein the first content is all the information displayed on the first display device;

interpreting a direction to move the content from the first display device based on the gesture; [[and]]

determining the destination display device to which the first content is to be moved based on the direction indicated by the gesture and the relative position of the plurality of display devices, wherein the destination display device is a second display device;

establishing a peer-to-peer connection between the first display device and the second display device;

propagating the first content of the first display device to the second display device using the peer-to-peer connection.

presenting the first content at the second display device, wherein a propagation order of the second content followed by the first content represents the sequence, wherein initiating the gesture simultaneously changes the content displayed at both the first display device and the second display device.

14. (Previously Presented): The computer readable medium of claim 13 wherein receiving input of the gesture includes:

receiving input on a touch screen display.

15-17. (Canceled)

18. (Previously Presented): The computer readable medium of claim 13 wherein presenting the first content at the second display device includes sending a first URL to the second display device.

19-20. (Canceled)

21. (Previously Presented): The system of claim 1, wherein the content of the third display device is automatically propagated on another display device in the plurality of display devices.

22-23. (Canceled)

24. (Previously Presented): The method of claim 5, wherein the content of the third display device is automatically presented to another display device in the plurality of display devices.

25-26. (Canceled)

27. (Currently Amended): The computer readable medium of claim 13, wherein the instructions further provide for the second content of the second display device to be automatically presented to ~~[[the]]~~ a third display device in the plurality of display devices.

28. (Currently Amended): The computer readable medium of claim 13, wherein the instructions further provide that ~~[[the]]~~ a third display device is in visual proximity to both the first display device and the second display device.

29. (Previously Presented): The computer readable medium of claim 28, wherein the instructions further provide that a content of the third display device is automatically presented to another display device in the plurality of display devices.

30. (Currently Amended): The computer readable medium of claim 18, wherein the instructions further provide that presenting the second content at ~~[[the]]~~ a third display device includes retrieving a second URL and sending the second URL to the third display device.

31. (Currently Amended): A system for providing content in a modular presentation system, comprising:

a plurality of display devices, wherein each display device includes a corresponding plurality of a processor and memory system to control each corresponding display device, and wherein each display device neighbors at least one other display device, wherein each display device is aware of the neighboring display devices, wherein each display device remains a discrete separately controlled display device;

a sequence of content including a first content and a second content;

an input device that receives input of a gesture to move a content from a first display device of the plurality of display devices, wherein the gesture is a movement from right to left

using a finger, wherein the movement from right to left specifies a starting point and a direction;
and

~~[[a]] wherein the processor corresponding to the first display device, that~~
interprets a direction to move the first content from the first display device based
on the gesture, ~~wherein the gesture does not designate a destination display device, that~~
~~specifies a second~~ determines the destination display device to which the first
content is to be moved, based on the direction indicated by the gesture and the position
of the plurality of display devices, wherein the destination display device is a second
display device, and that
establishes a peer-to-peer connection between the first display device and the
second display device,
propagates the first content of the first display device to the second display
device using the peer-to-peer connection, and automatically propagates the second
content of the second display device to a third display device of the plurality of display
devices,
wherein a propagation order of the second content followed by the first content
represents the sequence, wherein initiating the gesture changes the content displayed
on all of the first display device, the second display device and the third display device.

32. (Canceled)

33. (Previously Presented): The system of claim 1, wherein the gesture is made from a
device selected from the group consisting of keyboards, mouse devices, joysticks, microphones,
UV sensors, motion detectors and laser pointers.

34. (Previously Presented): The method of claim 5, wherein the gesture is made from a
device selected from the group consisting of keyboards, mouse devices, joysticks, microphones,
UV sensors, motion detectors and laser pointers.

35. (Previously Presented): The computer readable medium of claim 13, wherein the
gesture is made from a device selected from the group consisting of keyboards, mouse devices,
joysticks, microphones, UV sensors, motion detectors and laser pointers.

36. (Previously Presented): The system of claim 31, wherein the gesture is made from a device selected from the group consisting of keyboards, mouse devices, joysticks, microphones, UV sensors, motion detectors and laser pointers.
37. (Previously Presented): The system of claim 1, wherein the at least three display devices in visual proximity to each communicate through a server.
38. (Previously Presented): The method of claim 5, wherein the at least three display devices in visual proximity to each communicate through a server.
39. (Previously Presented): The system of claim 31, wherein the first display device, the second display device and the third display device each communicate through a server.
40. (Previously Presented): The system of claim 1, wherein the at least three display devices in visual proximity to each communicate through a peer to peer service.
41. (Previously Presented): The method of claim 5, wherein the at least three display devices in visual proximity to each communicate through a peer to peer service.
42. (Previously Presented): The system of claim 31, wherein the first display device, the second display device and the third display device each communicate through a peer to peer service.
43. (New) A system for providing a sequence of content in a modular presentation system, comprising:
- a plurality of display devices, wherein each display device includes a corresponding plurality of a processor and memory system to control each corresponding display device, and wherein each display device neighbors at least one other display device;
 - an input device that receives input of a gesture to move a first content from a first display device of the plurality of display devices to a second display device; and
 - wherein the processor corresponding to the first display device

interprets a direction to move the first content from the first display device based on the gesture, wherein the gesture is made with a flick which indicates content to be moved and a direction without designating a destination display device,

determines the destination display device to which the first content is to be moved, based on the direction indicated by the gesture and the position of the plurality of display devices, wherein the destination display device is the second display device,

establishes a peer-to-peer connection between the first display device and the second display device,

propagates the first content of the first display device to the second display device using the peer-to-peer connection, and

wherein initiating the gesture changes the content displayed on all of the first display device and the second display device.